


HOSE ASSEMBLIES FOR RETRACTABLE INJECTORS



SPECIFICATIONS

Hose assemblies are preassembled for easy ordering and ease of installation.

Each hose includes accessories for connection to your piping system.

- Choice of Hose or Tubing suitable for a wide range of chemicals
- Npt threaded Hose end fittings
- Female threaded coupling for connection and bushing (if needed) to connect to the retractable injector
- Check Valve (Optional)
- Ball Check Valve (Optional)

HOSE
Flexible Braided PVC tubing (rated for a minimum of 150 psi) Suitable for many water treatment chemicals including sodium hypochlorite, flocculants, algicides, coagulants
Sizes:
3/8" I.D.
1/2" I.D.
3/4" I.D.
PFA tubing (rated for 120 psi) Suitable for concentrated acid injection
Sizes:
1/4" I.D.
3/8" I.D.

BALL VALVES	
Stainless Steel	S
PVC	P
CPVC	C
PVDF (Kynar)	K
None	N

CHECK VALVES	
Stainless Steel	S
PVC	P
CPVC	C
PVDF (Kynar)	K
None	N



MODEL NUMBER

EXAMPLE "HA-P3/8X4-BVP-CVP"

HA-P3/8X4-BVP-CVP

HOSE	
Hose Length:	
<i>"X [hose length]" for example: "X3" would be 3 ft long.</i>	
Example:	
<i>"P1/2X3" would be a 3 ft long 1/2" flexible PVC hose assembly</i>	
Flexible Braided PVC tubing (rated for a minimum of 150 psi)	
Sizes	Code
3/8" I.D.	P3/8
1/2" I.D.	P1/2
3/4" I.D.	P3/4
PFA tubing (rated for 120 psi)	
Sizes	Code
1/4" I.D.	T1/4
3/8" I.D.	T3/8

CHECK VALVES	
Stainless Steel	S
PVC	P
CPVC	C
PVDF (Kynar)	K
None	N

BALL VALVES	
Stainless Steel	S
PVC	P
CPVC	C
PVDF (Kynar)	K
None	N

Examples of Model Number:

HA-P1/2X3-BVP-CVP would be a 1/2" braided PVC hose, 3 ft long with a 1/2" PVC ball valve for shut off and a 1/2"PVC check valve.

HA-P1/4X3.5-CVK would be a 1/4" PFA hose, 3-1/2 ft long with a PVDF check valve. No Ball Valve. (could also add a BVN code to signify no ball valve).

